ASTRAL HARDWAX

Page: 1

Compilation date: 12/01/2015

Professional Chemical Solutions

Revision date: 12/05/2015

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ASTRAL HARDWAX 150

Product code: AST-HARDWAX150

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: ASTRAL CSL

Pilkingtons Industrial Estate

Rake Lane

Clifton

Swinton

M27 8LP

United Kingdom

Tel: +44 (0) 161 643 0260

Fax: +44 (0) 870 199 2072

Email: sales@astralcsl.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 161 643 0260

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

SAFETY DATA SHEET ASTRAL HARDWAX

Page: 2

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

| EINECS | CAS | PBT / WEL | CLP Classification | Percent | |
|--------|-----|-----------|------------------------------|---------|--|
| - | - | - | Asp. Tox. 1: H304; -: EUH066 | 50-70% | |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

ASTRAL HARDWAX

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Workplace exposure limits:

| - | - | | • | |
|-------|------------|--------------|------------|--------------|
| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| EU | - | - | 1200 MG/M3 | - |

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Not applicable.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Not applicable.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Pale yellow

Odour: Pleasant

Evaporation rate: Negligible

Oxidising: Not applicable.

ASTRAL HARDWAX

| Solubility in water: | Insoluble | | |
|-------------------------------|--------------------|------------------------------|--------------------|
| Also soluble in: | hydrocarbons | | |
| Viscosity: | Not applicable. | | |
| Boiling point/range°C: | >35 | Melting point/range°C: | No data available. |
| Flammability limits %: lower: | Not applicable. | upper: | No data available. |
| Flash point°C: | 60 - 93 | Part.coeff. n-octanol/water: | No data available. |
| Autoflammability°C: | No data available. | Vapour pressure: | No data available. |
| Relative density: | 0.8 | pH: | 7 |
| VOC g/l: | No data available. | | |
| | | | |

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

| DERMA | L | RBT | LD50 | >5000 | mg/kg |
|-------|----|-----|---------|-------|-------|
| ORAL | | RAT | LD50 | >5000 | mg/kg |
| VAPOU | RS | RAT | 4H LC50 | >5000 | mg/l |

Page: 4

ASTRAL HARDWAX

Page: 5

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

| ALGAE | 72H IC50 | 20 | ppm |
|-------------------------------------|----------|-------|------|
| Daphnia magna | 48H EC50 | >1000 | mg/l |
| FISH | 96H LC50 | >1000 | ppm |
| RAINBOW TROUT (Oncorhynchus mykiss) | 96H LC50 | >250 | ppm |

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Not applicable.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

ASTRAL HARDWAX

Page: 6

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

| Other information | |
|------------------------------|--|
| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
| | 453/2010. |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and s.3: | EUH066: Repeated exposure may cause skin dryness or cracking. |
| | H304: May be fatal if swallowed and enters airways. |
| Legend to abbreviations: | PNEC = predicted no effect concentration |
| | DNEL = derived no effect level |
| | LD50 = median lethal dose |
| | LC50 = median lethal concentration |
| | EC50 = median effective concentration |
| | IC50 = median inhibitory concentration |
| | dw = dry weight |
| | bw = body weight |
| | cc = closed cup |
| | oc = open cup |
| | MUS = mouse |
| | GPG = guinea pig |
| | RBT = rabbit |
| | HAM = hamster |
| | HMN = human |
| | MAM = mammal |
| | PGN = pigeon |
| | IVN = intravenous |
| | SCU = subcutaneous |
| | SKN = skin |
| | DRM = dermal |
| | OCC = ocular/corneal |
| | OPT = optical |
| | INH = inhalation |
| | PCP = physico-chemical properties |
| Legal disclaimer: | The above information is believed to be correct but does not purport to be all inclusive |

ASTRAL HARDWAX

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Page: 7