

SAFETY DATA SHEET

AIR REFRESH

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME AIR REFRESH  
 PRODUCT NO. AJARB  
 SUPPLIER Astral Chemical Solutions Ltd.  
 P.O. Box 250  
 Whitefield  
 Manchester M45 8XQ  
 Tel: 0161 767 8219



**EMERGENCY TELEPHONES (+0044) (0) 161 620 5400 NOTE: TO BE USED FOR CHEMICAL EMERGENCIES ONLY!!!**

2 COMPOSITION/INFORMATION ON INGREDIENTS

| Name        | EC No.    | CAS-No. | Content | Classification   |
|-------------|-----------|---------|---------|------------------|
| PROPAN-2-OL | 200-661-7 | 67-63-0 | < 1%    | F;R11 Xi;R36 R67 |

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name        | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|-------------|-----|----------|------------|----------|------------|
| PROPAN-2-OL | WEL | 400 ppm  | 999 mg/m3  | 500 ppm  | 1250 mg/m3 |

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT

**AIR REFRESH**



**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**HAND PROTECTION**

For prolonged or repeated skin contact use suitable protective gloves.

**EYE PROTECTION**

Wear approved chemical safety goggles where eye exposure is reasonably probable.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

|                  |                   |                  |         |
|------------------|-------------------|------------------|---------|
| APPEARANCE       | Liquid            |                  |         |
| COLOUR           | White             |                  |         |
| ODOUR            | Characteristic    |                  |         |
| SOLUBILITY       | Soluble in water. |                  |         |
| RELATIVE DENSITY | 1.0 @20           | FLASH POINT (°C) | na N/A. |

**10 STABILITY AND REACTIVITY**

**STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

**11 TOXICOLOGICAL INFORMATION**

**INHALATION**

Gas or vapour may irritate respiratory system.

**INGESTION**

Gastrointestinal symptoms, including upset stomach.

**SKIN CONTACT**

Prolonged contact may cause dryness of the skin.

**EYE CONTACT**

Irritating to eyes.

**HEALTH WARNINGS**

No specific health warnings noted.

**ROUTE OF ENTRY**

Ingestion. Inhalation. Skin and/or eye contact.

**12 ECOLOGICAL INFORMATION**

**ECOTOXICITY**

Not regarded as dangerous for the environment.

**13 DISPOSAL CONSIDERATIONS**

**AIR REFRESH**

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

---

14 TRANSPORT INFORMATION

---

|                      |  |
|----------------------|--|
| GENERAL              | The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).<br>No transport warning sign required. |
| RAIL TRANSPORT NOTES | Not Classified.  |
| SEA TRANSPORT NOTES  | Not Classified.  |
| AIR TRANSPORT NOTES  | Not Classified.  |
| MARINE POLLUTANT     | No.  |

---

15 REGULATORY INFORMATION

---

|                |     |   |
|----------------|-----|---|
| RISK PHRASES   | NC  | Not classified.   |
| SAFETY PHRASES | S2  | Keep out of the reach of children   |
|                | S46 | If swallowed, seek medical advice immediately and show this container or label. |

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

---

16 OTHER INFORMATION

---

INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION DATE 24/08/2006

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL

|     |   |
|-----|---|
| R11 | Highly flammable.                           |
| R36 | Irritating to eyes.                         |
| R67 | Vapours may cause drowsiness and dizziness. |

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.