

SAFETY DATA SHEET  
SOLVENT DEGREASER

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

PRODUCT NAME SOLVENT DEGREASER  
 PRODUCT NO. AJSSV-16  
 SUPPLIER Astral Chemical Solutions Ltd  
 PO Box 250  
 Whitefield  
 Manchester  
 0161 767 8219



**EMERGENCY TELEPHONES (+0044) (0) 161 620 5400**

**NOTE: TO BE USED FOR CHEMICAL EMERGENCIES ONLY!!!**

**2 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	5-10%	F+;R12
ISOBUTANE	200-857-2	75-28-5	1-5%	F+;R12
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT	265-151-9	64742-49-0	30-60%	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67
PROPANE	200-827-9	74-98-6	10-30%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

**3 HAZARDS IDENTIFICATION**

Extremely flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R36/38. F+;R12. N;R51/53. R67.

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

**INHALATION**

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

**INGESTION**

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

**SKIN CONTACT**

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire.

**6 ACCIDENTAL RELEASE MEASURES**

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

**SOLVENT DEGREASER**

**7 HANDLING AND STORAGE**

**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3
ISOBUTANE	WEL	800 ppm		800 ppm	
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT			1200 mg/m3		

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT**



**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. Use chemical cartridge protection with appropriate cartridge.

**HAND PROTECTION**

Use protective gloves.

**EYE PROTECTION**

Use approved safety goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Aerosol		
COLOUR	Colourless		
ODOUR	Characteristic		
SOLUBILITY	Insoluble in water		
FLAMMABILITY LIMIT - LOWER(%)	0.8	FLAMMABILITY LIMIT - UPPER(%)	9.0

**10 STABILITY AND REACTIVITY**

**STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

**SOLVENT DEGREASER**

**11 TOXICOLOGICAL INFORMATION**

**INHALATION**

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

**INGESTION**

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

**SKIN CONTACT**

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

**EYE CONTACT**

Irritating to eyes. May cause chemical eye burns.

**ROUTE OF ENTRY**

Inhalation. Skin and/or eye contact.

**12 ECOLOGICAL INFORMATION**

**ECOTOXICITY**

Dangerous for the environment if discharged into watercourses.

**13 DISPOSAL CONSIDERATIONS**

**DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**



UK ROAD CLASS	2		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2	ADR CLASS	Class 2: Gases
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2	IMDG PACK GR.	Not Applicable
EMS	F-D, S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	Not Applicable

**15 REGULATORY INFORMATION**

**LABELLING**



Irritant



Extremely Flammable



Dangerous for the environment

**RISK PHRASES**

R12	Extremely flammable.
R36/38	Irritating to eyes and skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SOLVENT DEGREASER**

R67	Vapours may cause drowsiness and dizziness.
SAFETY PHRASES	
S2	Keep out of the reach of children
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

**16 OTHER INFORMATION**

REVISION DATE 24/08/2006

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL

R11	Highly flammable.
R12	Extremely flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.