

## SAFETY DATA SHEET CUTTING TAPPING & DRILLING SPRAY

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name CUTTING TAPPING & DRILLING SPRAY  
Product No. A S T- CTD400

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier ASTRAL CSL  
Pilkington Industrial Estate  
Rake Lane  
Swinton  
M27 8LP  
England  
TEL:0161 643 0260 FAX:0870 199 2072  
sales@astralcsl.com



#### 1.4. Emergency telephone number: 0161 643 0260

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

|                               |                               |                          |
|-------------------------------|-------------------------------|--------------------------|
| Classification (EC 1272/2008) | Physical and Chemical Hazards | Flam. Aerosol 1 - H222   |
|                               | Human health                  | Lact. - H362             |
|                               | Environment                   | Aquatic Chronic 2 - H411 |
| Classification (1999/45/EEC)  | F+;R12. N;R51/53. R64.        |                          |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

|      |  |
|------|--|
| H222 | Extremely flammable aerosol.                     |
| H362 | May cause harm to breast-fed children.           |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary Statements

|      |   |
|------|---|
| P102 | Keep out of reach of children.                                      |
| P263 | Avoid contact during pregnancy/while nursing.                       |
| P261 | Avoid breathing vapour/spray.                                       |
| P271 | Use only outdoors or in a well-ventilated area.                     |
| P501 | Dispose of contents/container in accordance with local regulations. |

Supplementary Precautionary Statements

|      |  |
|------|--|
| P201 | Obtain special instructions before use.                            |
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P211 | Do not spray on an open flame or other ignition source.            |
| P251 | Pressurized container: Do not pierce or burn, even after use.      |
| P270 | Do not eat, drink or smoke when using this product.                |
| P273 | Avoid release to the environment.                                  |
| P264 | Wash contaminated skin thoroughly after handling.                  |

## CUTTING TAPPING & DRILLING SPRAY

P308+313

IF exposed or concerned: Get medical advice/attention.

P391

Collect spillage.

P410+412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

|   |  |
|---|--|
| BUTANE  | 1-5%                                     |
| CAS-No.: 106-97-8   | EC No.: 203-448-7                        |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220                               | Classification (67/548/EEC)<br>F+;R12    |
| CHLORINATED PARAFFIN C14-C17 (51%)  | 10-30%                                   |
| CAS-No.: 85535-85-9   | EC No.: 287-477-0                        |
| Classification (EC 1272/2008)<br>EUH066<br>Lact. - H362<br>Aquatic Acute 1 - H400 | Classification (67/548/EEC)<br>N;R50/53. |
| ISOBUTANE   | 1-5%                                     |
| CAS-No.: 75-28-5  | EC No.: 200-857-2                        |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220                               | Classification (67/548/EEC)<br>F+;R12    |
| PROPANE   | 5-10%                                    |
| CAS-No.: 74-98-6  | EC No.: 200-827-9                        |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220                               | Classification (67/548/EEC)<br>F+;R12    |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

**DO NOT INDUCE VOMITING!** Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

#### Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

# CUTTING TAPPING & DRILLING SPRAY

## Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## 4.2. Most important symptoms and effects, both acute and delayed

## 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### 5.2. Special hazards arising from the substance or mixture

#### Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

### 6.4. Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### 7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

| Name      | STD | TWA - 8 Hrs  |               | STEL - 15 Min |               | Notes |
|-----------|-----|--------------|---------------|---------------|---------------|-------|
|           |     |              |               |               |               |       |
| BUTANE    | WEL | 600 ppm      | 1450 mg/m3    | 750 ppm       | 1810 mg/m3    |       |
| ISOBUTANE | WEL | 800 ppm      |               | 800 ppm       |               |       |
| PROPANE   |     | Asphyxiating | Asphyxiating. | Asphyxiating  | Asphyxiating. |       |

#### Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

# CUTTING TAPPING & DRILLING SPRAY

## Protective equipment



## Engineering measures

Provide adequate general and local exhaust ventilation.

## Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

## Hand protection

Use protective gloves.

## Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

## Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                               |                    |
|-------------------------------|--------------------|
| Appearance                    | Aerosol.           |
| Colour                        | Brown.             |
| Odour                         | Characteristic.    |
| Solubility                    | Insoluble in water |
| Flammability Limit - Lower(%) | 0.8                |
| Flammability Limit - Upper(%) | 9.0                |

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

# CUTTING TAPPING & DRILLING SPRAY

## Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

## Eye contact

Irritating to eyes. May cause chemical eye burns.

## Route of entry

Inhalation. Skin and/or eye contact.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

|                      |      |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1950 |
| UN No. (IMDG)        | 1950 |
| UN No. (ICAO)        | 1950 |

### 14.2. UN proper shipping name

|                      |          |
|----------------------|----------|
| Proper Shipping Name | AEROSOLS |
|----------------------|----------|

### 14.3. Transport hazard class(es)

|                     |                |
|---------------------|----------------|
| ADR/RID/ADN Class   | 2              |
| ADR/RID/ADN Class   | Class 2: Gases |
| ADR Label No.       | 2.1            |
| IMDG Class          | 2.1            |
| ICAO Class/Division | 2.1            |
| Transport Labels    |                |



### 14.4. Packing group

## CUTTING TAPPING & DRILLING SPRAY

|                           |     |
|---------------------------|-----|
| ADR/RID/ADN Packing group | N/A |
| IMDG Packing group        | N/A |
| ICAO Packing group        | N/A |

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant  
No.

### 14.6. Special precautions for user

|                         |          |
|-------------------------|----------|
| EMS                     | F-D, S-U |
| Tunnel Restriction Code | (D)      |

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

#### Statutory Instruments

Control of Substances Hazardous to Health.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I. 2009 No. 716).

#### Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

### 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

Revision Date 20/05/2010

Revision 8

#### Risk Phrases In Full

R12 Extremely flammable.

R64 May cause harm to breastfed babies.

R66 Repeated exposure may cause skin dryness or cracking.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Hazard Statements In Full

H222 Extremely flammable aerosol.

H220 Extremely flammable gas.

H362 May cause harm to breast-fed children.

EUH066 Repeated exposure may cause skin dryness or cracking.

H411 Toxic to aquatic life with long lasting effects.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his

